

ERFARINGER FRA UDLANDET MED KVALITETS- OG PERFORMANCEKONTROL, MÅLEMETODER OG LANGTIDSMONITERING

Geosyntec

consultants

engineers | scientists | innovators

Vintermøde 2019, Temadag
om Soil Mixing som
afværgemetode



Per Lindh, Ph.D.

Trafikverket

per.lindh@trafikverket.se

Christopher A. Robb, P.E. (WI and FL)

Principal Engineer

Geosyntec Consultants, Inc.

crobb@Geosyntec.com

March 4, 2019

- **An effective quality program is critical to the success of an ISS or ISS/IST project**
 - Benefits from personnel experienced with specific ISS/IST quality and performance control
- **Goal: Rapidly Assess ISS/IST Performance and Identify Potential Construction Issues**

- A well planned quality program has two elements:
 - **Contractor QC program:** Provides the construction procedures and material handling requirements that ensure the design requirements for the treatment are met
 - **Owner QA program:** Provides for monitoring, sampling, and testing procedures to verify that the treatment meets the design requirements
- Key elements of an effective QC/QA program
 - Contractor QC Procedures
 - Contractor QC documentation
 - Construction Quality Assurance (CQA) Procedures
 - CQA Sampling

WHY IS CONTRACTOR QC IMPORTANT?


- **CONTRACTOR VERIFIES CONSTRUCTION IN ACCORDANCE WITH DESIGN REQUIREMENTS**
- Contractors Typically Provide:
 - Layout for ISS Treatment Areas and Columns
 - Equipment for ISS CQA Sampling
 - Survey Control for ISS Column Locations and Record Documentation
 - Field Engineer's Notes
 - Daily Deliverables:
 - Batch Plant QC and Mix Verification Logs
 - Delivery Receipts for ISS and Materials
 - Drill Rig QC Report
 - ISS Column Logs
- Batch plant operational parameters
- Mix equipment operational parameters
 - mixing time
 - mixing speed
 - auger diameter
 - column depth
 - column location
 - number of passes
 - grout flow rate
 - rotary head pressure
 - quantity of grout (i.e., Reagents, Additives and water)

Quality Control Tools

- QC Equipment calibration
- Scale calibration
- Mud balance
- Flow meter
- GPS / total station




Layout for ISS/IST Treatment Areas and Columns



Drill Rig -Electronic Data Acquisition

- **ELECTRONIC REPORTING:**

- TIME
- DATE
- COLUMN IDENTIFICATION
- GROUT FLOW RATE
- TOTAL GROUT INJECTION
- PENETRATION DEPTH
- INCLINATION (DEGREE)
- ROTATIONS PER MINUTE (RPM)
- PENETRATION RATE/ WITHDRAWAL SPEED/ (# OF STROKES)
- ROTARY HEAD PRESSURE (DRILLING RESISTANCE)



- **DEPTH**
- **Grout Flow**
- **Rotary Pressure**
- **Down stroke**
- **Up stroke**

Drill Rig QC Report

- Mix equipment operational parameters:
 - mixing time
 - mixing speed
 - auger diameter
 - column depth
 - column location
 - number of passes
 - grout flow rate
 - rotary head pressure
 - quantity of grout (i.e., reagents, additives, water)



KVALITETSSIKRING
SKEMA NR. S.3.03.04.54 KS-skema
På denne måde vil du sikre

ARKIL

Form	Solubilitet af boksene	Segment	Såfald skema
Skema nr.	13	Est. segment	2810244
Skema		Est.	750

Date: 23.06.2018 Start miksning (d) 14.30 Slut miksning (d) 16.30

Mixing Fra (min) 5 Til (min) 10

Mixing total meter / volumer 5 15.708

Aerial overboring / volumer / direction Længde 2.2701 m 8 0

Samlet volumer til miksning 15.708

Recept fra flyve Cement (kg) 2312 Klorur (L) 2892

247.2 kg/m³ 105.15

Aftalt procedure for soilmixing i de enkelte cyklusser (som G8 og D6 i pilottest)

Cyklus nr.	Penetrering i meter/min	Samlet minutter	Rotation omdr/min	Bemærkning
3-DOWN	0,2	25	32	+ Tilsæt cementslorry
1-UP	0,3	17	32	Kun miksning
2-DOWN	0,3	17	32	+ Tilsæt 50% Klorur
2-UP	0,3	17	32	+ Tilsæt 50% Klorur
3-DOWN	0,50,3	10	32	Kun miksning
1-UP	0,50,3	10	32	Kun miksning

Drift Klorurpumpe til hele 2. cyklus 28,5 Hz 22.66 Omdr/min

Drift Cementtilførsning i 1-DOWN 52,5 kg/min 1,54 kg/sek

Faktisk tilførsel mængder i kolonne

Cement 2312 Kg Vand 2455 Liter Klorur 2892 Liter

Notater: Pensulfat tilsat 2 cyk. ned og 3 cyk. ned
Penetrering sat til 0,3 ned i stedet for 0,5
i 3 cyk. ned pga. utætte borehul

Cyklus nr.	Penetrering i meter/min	Samlet minutter	Rotation omdr/min	Bemærkning
1-DOWN	0,2	25	10	+ Tilsæt cementslorry
1-UP	0,3	17	32	Kun mixing
2-DOWN	0,3	17	32	+ Tilsæt 50% klorur
2-UP	0,3	17	32	+ Tilsæt 50% klorur
3-DOWN	0,50,3	10	32	Kun mixing
3-UP	0,50,3	10	32	Kun mixing

Production Report

	Excavation CY	Slag TONS	Cement TONS	Bentonite TONS
Total Today	17.62	1.89	0.94	0.00
Total To-Date	17.62	1.89	0.94	0.00

- Confirm design parameters
 - Cumulative reporting
 - Confirm reagents
 - Confirm depths

ACTUAL		
Top of Col	Bottom of Col	As-Built Depth
ELEV	ELEV	FT
542.22	533.22	9.00


Calculated Slag Addition* Target -%		Calculated Cement Addition* Target -%		Calculated Bentonite Addition* Target -%	
<i>LBS</i>	<i>%</i>	<i>LBS</i>	<i>%</i>	<i>LBS</i>	<i>%</i>
3,780	7.94%	1,880	3.95%	#N/A	#N/A

WHY IS CQA IMPORTANT?

- **OWNER VERIFIES CONSTRUCTED IN ACCORDANCE WITH DESIGN REQUIREMENTS**
- **Goal: Rapidly Assess ISS Performance and Identify Potential Construction Issues**
- **Owner CQA Includes:**
 - Collection of ISS CQA Samples to Verify Treatment (e.g., Field Parameters, UCS and K)
 - Daily Reviews:
 - Batch Plant Logs, Production Logs and ISS Column Logs
 - Visual Assessment of ISS Mixing
 - Review Survey Control
 - Review Field Engineer's Notes as Needed



Hydraulic Sampler



“Trap Door” Sampler



Source: Modified from Robb, C. “Evaluation of *In Situ* Stabilization/Solidification Discrete Zone Applications for Subsurface Soils” June 2010

CQA SAMPLE PROCESSING

- Verification of homogenous mixing
- Field measurement parameters: moisture content, pH, temperature
- Field Observations: unmixed clods, color/ consistency, free phase NAPL
- Screening and molding CQA samples
- Curing samples



- Performance criteria based on bench and pilot scale results
 - UCS, Hydraulic Conductivity, Durability (if necessary)
 - *Leaching performance correlated with physical performance at the bench scale level*
- High testing frequency for UCS, hydraulic conductivity
 - One sample every 500 – 1,000 m³, higher frequency for smaller projects
 - One sample/day minimum
- Low testing frequency for durability
 - One sample every 5,000 m³
- Additional testing around sensitive structures/areas

- Unconfined Compressive Strength (UCS) [ASTM D1633 or D2166]:
 - 50 psi [0.345 MPa] (common in USA)
 - Can design to increase/decrease UCS
- Hydraulic Conductivity (K) [ASTM D5084]:
 - $< 1 \times 10^{-6}$ cm/s to 1×10^{-7} cm/s
 - 1 to 2 orders of magnitude less than native material K is desired
- Leaching [SW-846 LEAF Method 1315]:
 - Determine interval flux; cumulative release to estimate mass transfer – What are your COCs / Receptors?
- Durability [ASTM D4843 and ASTM C1262]:
 - Wet/Dry – Freeze/Thaw $< 10\%$ to 15% degradation after 12 cycles
 - May not be necessary
- Contaminant Destruction



Source: *Development of Performance Specifications for Solidification/Stabilization*, Interstate Technology & Regulatory Council (ITRC), July 2011.

- Environmental monitoring
 - Turbidity and pH monitoring
 - Air Monitoring
- Structural monitoring
 - Deflection
 - Settlement
 - Deformation
- Alternatives for in situ CQA sampling:
 - Coring
 - Useful for uniformity
 - Need high core recovery w/ low disturbance for strength
 - 2-3 week cure before sampling
 - Coarse soils may prevent acceptable core recovery
 - Not suitable for permeability
 - Expensive – Time Consuming
- In situ direct testing (e.g., CPT, Vane Shear)
- Geophysical Testing (e.g., PS logging)


- Establish Conceptual Site Model (CSM)
- **Objective:** estimate the possible impact to an underlying aquifer of various ISS/IST remediation strategies, typically in terms of possible impacts on groundwater conditions immediately around a source zone and at some distance downgradient of the impacted area where one or more receptors may exist (i.e., Point of Compliance – POC)

Considerations for CSM - ISS/IST

S/S evaluation factor	Analyses/observations	Significance to technology performance and monitoring
Soil classification/ physical characteristics	Useful measurements: <ul style="list-style-type: none"> • Gradation • Unified Soil Classification System (USCS) classification • Atterberg limits • Moisture content • Debris content • Porosity • Density • Suspended solids • Free liquid (pore filter) 	Property values for each measurement and their variability may have significant impact of overall behavior of the S/S material and on expected outcomes
Soil and groundwater	pH	Controlling variable for inorganic solubility and S/S material durability
Geochemistry	Organic content	Key variable for organic concentrations due to complexation with DOC, which is soluble at high pH (Roskam and Comans 2003, 2007)
	Contaminant levels	High concentrations of some contaminants may affect S/S cure, requiring additives to overcome interference (Conner 1997)
	Sulfate content	Sulfate attack of portland cement blends may lead to aggressive degradation through delayed ettringite formation (Little, Herbert, and Kungalli 2005)
Contaminant characterization	Leaching behavior of untreated material	Defines baseline against which treatability studies and full-scale application may be compared
	Class(es) of contaminants	Defines list of COCs, defines detection limits for analysis
	Presence/distribution of NAPLs	Defines phases/location of source and expected outcomes
Hydrogeology	Hydraulic conductivity	Controlling value in comparison to hydraulic conductivity of S/S material for mode of water contact (e.g., infiltration vs. flow-around)
	Water table depth and seasonal variability	Defines division between vadose zone, capillary fringe, and saturated zone; NAPL impacts at water table
	Geologic strata (including geometry of geology units)	Location of contaminant distribution/accumulation zones
	Groundwater flow direction and gradients	Hydraulic head on S/S mass, evaluate fate and transport with respect to POC

Source: *Development of Performance Specifications for Solidification/Stabilization*, Interstate Technology & Regulatory Council (ITRC), July 2011

Prediction Methods – Simple to Complex



- **Steady state attenuation along the centerline of a groundwater plume**
- $C_{(x)}$ = Concentration of Contaminant in Groundwater at Distance X from the source (mg/L)
- C_{source} = greatest potential concentration of the contaminant of concern in the groundwater at the source of the contamination (leaching from ISS/IST)

Equation R26 – 35 IAC 742 Tiered Approach to Corrective Action Objectives

$C_{(x)} =$

$$C_{source} \cdot \exp \left[\left(\frac{X}{2\alpha_x} \right) \cdot \left(1 - \sqrt{1 + \frac{4\lambda \cdot \alpha_x}{U}} \right) \right] \cdot \operatorname{erf} \left[\frac{S_w}{4 \cdot \sqrt{\alpha_y \cdot X}} \right] \cdot \operatorname{erf} \left[\frac{S_d}{2 \cdot \sqrt{\alpha_z \cdot X}} \right]$$

NOTE:

1. This equation does not predict the contaminant flow within bedrock and may not accurately predict downgradient concentrations in the presence of a confining layer.
2. If the value of the First Order Degradation Constant (λ) is not readily available, then set $\lambda = 0$.

- Longitudinal Dispersivity

$$\alpha_x = 0.10 \cdot X$$

-

- Transverse Dispersivity

$$\alpha_y = \frac{\alpha_x}{3}$$


- Vertical Dispersivity

$$\alpha_z = \frac{\alpha_x}{20}$$

- Error Function

$$\operatorname{erf}(\beta) = \frac{2}{\sqrt{\pi}} \int_0^{\beta} e^{-\varepsilon^2} d\varepsilon$$

Mass Flux Approximation Model




$$C_n = \frac{F \cdot A_{exp}}{A_n \cdot q}$$

- C_n – concentration in groundwater (mg/L)
- F – mass flux, leach testing ($mg/m^2 s$)
- A_{exp} – exposed surface area of the treated material (m^2)
- A_n – cross-sectional area of groundwater (m^2)
- q – groundwater flow rate (m/d)


Source: Modified from *Development of Performance Specifications for Solidification/Stabilization*, Interstate Technology & Regulatory Council (ITRC), July 2011

- Relate to a concentration (C_{POC}) at the POC through a dilution-attenuation factor (DAF)
- Accommodate surface water infiltration




- **Yellow – Purple – Green:** ISS
- **Green** – Cloud Branch Creek
- **Orange** – Stormwater Features
- **Blue contours** – Predicted increase in groundwater elevation
- **Light Blue** – Groundwater expressed at ground surface

Source: Hennings, B. G., C. A. Robb, and R. E. Wittenberg. 2011. Draft In Situ Stabilization/Solidification Design Considerations and Applications for Groundwater Modeling. Natural Resource Technology, Technical Memorandum. *Development of Performance Specifications for Solidification/Stabilization*, Interstate Technology & Regulatory Council (ITRC), July 2011



- **Particle tracking - MODPATH**
- Upgradient - travel toward the ISS and captured by the groundwater relief drains or travel along the edge of the monolith until they reached the stream as it exited the box culvert
- Downstream - move very closely along the ISS and be captured within 60 m of the downstream edge of the monolith

Source: Hennings, B. G., C. A. Robb, and R. E. Wittenberg. 2011. Draft In Situ Stabilization/Solidification Design Considerations and Applications for Groundwater Modeling. Natural Resource Technology, Technical Memorandum. *Development of Performance Specifications for Solidification/Stabilization*, Interstate Technology & Regulatory Council (ITRC), July 2011




- **Groundwater Network**
- Side-gradient wells located in close proximity along the length of the ISS
- Combine with wells located directly downgradient of the ISS
- Verify with groundwater screening program
- Approximate groundwater monitoring well locations

Source: Modified from Hennings, B. G., C. A. Robb, and R. E. Wittenberg. 2011. Draft In Situ Stabilization/Solidification Design Considerations and Applications for Groundwater Modeling. Natural Resource Technology, Technical Memorandum. *Development of Performance Specifications for Solidification/Stabilization*, Interstate Technology & Regulatory Council (ITRC), July 2011

In-situ sampling




Non destructive testing




Why should we use this ?

The same properties are measured
in lab and in-situ



Evaluation of Shear wave



P-wave as a function of strength




Maturity index




In-situ seismic measurement



Evaluation of in-situ seismic measurement




Core sampling



Cross-hole seismic



Results from cross-hole seismic



Thank you for your time!

Per Lindh, Ph.D.

Trafikverket

per.lindh@trafikverket.se

Christopher A. Robb, P.E.

Geosyntec Consultants, Inc.

crobb@Geosyntec.com

Acknowledgements:

Neal Durant, Ph.D.

Dogus Meric, Ph.D., P.E.

Dan Woeste, P.E.